

HT-4600E

www.posiflex.com

POSIFLEX
Your Success is Our Vision



Specification	HT-4612HX-E	HT-4612X
Processor	Intel Pentium Dual Core 2.3 GHz / 1 MB Cache CPU or Intel Core 2 Duo 2.26 ~ 2.53 GHz / 3 ~ 6 MB Cache CPU	
System Memory	DDR3 1066 MHz, SO-DIMM socket x 2, max 8 GB, default 1 GB	
Storage Device	2.5" SATA HDD or SSD Kit (Optional)	
Power Supply	12V DC power adaptor, 80W	
Audio	Line out / Mic in, 1 W speaker (Optional)	
OS support	Win 7 / Win XP Pro / POSReady 7 / Linux	
Color	Ivory white or Black	
LCD		
LCD	12" TFT LCD, 1024 x 768 resolution	
Touch Function	Resistive, 5-wire, USB interface	N/A
Brightness Control	By rotary dial	
Tilt Adjustment	From 40° to 75°	
Connectivity		
CF Card Slot	N/A	
LAN Port	10 / 100 / 1000 Mb	
Parallel Port	Yes	
Serial Port	DB9 x 4, with 5V / 12V support on COM1 / COM2 / COM3 COM4	
PS/2 Keyboard	Yes	
PS/2 Mouse	Yes	
Extension Slot	PCI slot x 1, for half length PCI card	
UPS Port	N/A	
Standard USB Port	6	
VGA Port		
CR Port	1, control 2 CR	
Physical Dimension		
Dimension (W x D x H in mm)	295 X 264 X 341	
Weight (N. W. in kg)	5.6	5.3
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
Options		
SSD	8 GB minimum	
CF Card	N/A	
2nd HDD	Yes	
RAID Function	Support RAID 1 (Disk mirroring)	
PU-430	Powered USB board, 24V X1 port, upgraded adaptor to 150W (PU-430 and HT-022 can't coexist)	
HT-022	COM5/COM6 adaptor board, with 5V support (PU-430 and HT-022 can't coexist)	
UPS Battery	N/A	
2nd LCD Display	10.4" LM-2010, 12" LM-7112, 12" touch TM-7112	
PD-307 / PD-307U	2 x 20 LCD, default 200 mm pole	
PD-2601 / PD-2601U	2 x 20 VFD, default 200 mm pole	
PD-76X1	240 x 64 dots graphics LCD, default 200 mm pole	
PD-7321	160 x 32 dots graphics LCD, default 200 mm pole	
KP-200	Side mount programmable keypad with optional MSR and smart card reader	
SD-366	3 tracks or JIS-II, optional fingerprint sensor	
Options		

HT-4600E

Advanced Compact POS Terminal



Design and Manufacturing In Taiwan by Posiflex Technology Inc. 2013 HT46Q1C1
 ** The product information and specifications are subject to change without prior notice.

POSIFLEX Posiflex Technology, Inc.
 Headquarters
 No.6, Wuquan Rd., Wugu Dist., New Taipei City
 248, Taiwan (R.O.C.)
 Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
 sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com