

Epson

Mobilink™

Wireless Printer



Get all the great features of Epson's best-selling TM-T88 thermal POS printer in the compact and cost-effective Mobilink wireless printer.

Built with Epson's famous quality and reliability, the Mobilink is designed to meet the needs of both retail, food service and logistics for uninterrupted, high-speed, on-the-go thermal receipt and label printing.

Great features go mobile

Whether you need a receipt or label printer for use in retail, food service, pharmacies, route accounting or distribution centers, Epson's Mobilink wireless printer comes with all the features you need. It's the fastest printer in its class and offers clear, crisp printing, drop-in paper loading and a ruggedized design to ensure reliability in even the harshest environments.

Your choice of models

With Mobilink you can have your choice of wireless interfaces. Both Mobilink receipt and label printers are available with Bluetooth® and 802.11g with IEEE 802.11i security and advanced EAP-TLS authentication for fast and easy integration. The receipt printer also includes an autocutter and the label printer includes a label peeler.

Best-in-class battery life

Unlike other wireless printers with an average battery life of 2-3 hours, the Mobilink features an industry-leading

battery life of up to 10 hours with 802.11g models and up to 20 hours with Bluetooth models.

Compatible and ready to go

Epson's Mobilink wireless printer is compatible with today's best-of-breed and component-based POS systems and industry-standard wireless security protocols. The printer comes complete with ESC/POS®, OPOS, JPOS and Windows® drivers which means your current applications are instantly compatible. And a Zebra emulation is available for drop-in replacements. Mobilink is also compatible with leading business label software applications when using Windows drivers.

Flexible wireless printing

Mobilink offers flexible, high-speed printing, network support and superior reliability with an extremely low total cost of ownership. It also comes with the required integration tools you need to easily configure the printer on site.

- Industry-leading battery life up to 20 hours
- Compact size with ruggedized 6-foot drop rating
- Highest speed thermal printing in its class
- Supports Bluetooth® and 802.11g with IEEE 802.11i security and advanced EAP-TLS authentication
- Print width up to 54mm accommodates more text
- 58mm paper width enables use of standard off-the-shelf media
- Zebra® emulation for drop-in replacements



There is also a label printer model for fast, on-demand printing for label applications.

Epson Mobilink™ Wireless Printer

Printer Specifications

| | | |
|-----------------------|---------------------|--------------------------------------------------------------------------------------------------------------------------|
| General | Print method | Thermal line printing |
| | Dot/line | 420/432 dots |
| | Print font | |
| | Font | Font A 12 x 24, new Font B 10 x 24, new Font C 8 x 16 |
| | Column capacity | 58mm paper, Font A/B/C, 35/42/52 columns; 60mm paper, Font A/B/C, 36/43/54 columns |
| | Character size | 1.5(W) x 3.0(H)/1.25(W) x 3.0(H)/1.0(W) x 2.0(H)mm |
| | Character set | 95 Alphanumeric, 48 International, 128 x 10 Graphic |
| | Bar code | UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), CODE 39, CODE 93, CODE 128, ITF, CODABAR, 2D bar codes: PDF417, QR CODE, MAXICODE |
| | Characters per inch | 17/20/25 cpi |
| | Printer | Interface |
| Data buffer | | 128 bytes |
| Print speed (max.) | | Receipt version 70mm/second, label version 80mm/second |
| Paper width | | Paper or labels, 58mm or 60mm width (receipt version) Paper or labels, 30–60mm (label version) |
| Paper diameter (max.) | | 51 mm |
| Autocutter | | Partial cut, left uncut (receipt version) |
| Peeler | | Automatic label removal from backing (label version) |
| Audible alert | | Programmable buzzer |
| Sensors | | Paper out (receipt and label versions) Gap, black mark, label taken (label version) |
| Indicators | | Battery charge level, wireless connection status, error condition |
| Software | | Browser-based configuration and proprietary remote wireless management tools |
| Power | | Custom Lithium-Ion battery pack, AC adapter (option) |
| Charging | | AC adapter (4 hours to full charge), custom external charger (2.5 hours to full charge) |
| Reliability | | 10 million printing lines 500,000 autocutter |
| Operating temperature | | 0° C to 50° C |
| Drop | | Drop test rating of 6 feet |
| Battery life | | Up to 10 hours with 802.11g, up to 20 hours with Bluetooth |
| Overall dimensions | | 103 x 159 x 65mm (W x D x H) {4.05 x 6.25 x 2.55"} |
| Weight | | Receipt version 670g with battery, label version 640g with battery |
| Control Board | | EMC standards |
| | Safety standards | UL, CSA, TÜV (EN60950) |

