

Specification	FT-7715I / RAID	FT-7715 / RAID
Processor	Intel B81X 1.6GHz / 2 M cache CPU Intel B950 2.1GHz / 2 M cache CPU Intel Core i3 2.2GHz / 3 M cache CPU Intel Core i5 2.5GHz / 3 M cache CPU	
System Memory	DDR3 1066 / 1333 MHz, SO-DIMM socket x 2, max 8 GB, default 4 GB	
Storage Device	2.5" SATA HDD or SSD (Optional)	
Power Supply	12V DC power adaptor, 80W	
Audio	2W speaker x 2, line out	
OS support	Win 7 / Win XP Pro / POSReady 7 / POSReady 2009	
Color	Black	
Display		
LCD	15" TFT LCD, LED backlight, 1024 x 768 resolution	
Touch Function	IR touch, USB interface	Resistive, 5-wire, USB interface
Brightness Control	By push button	
Tilt Adjustment	From 20° to 45°	
Connectivity		
LAN Port	10 / 100 / 1000 Mb	
CFAST	Yes, Type I	
Serial Port	DB9 x 4, with 5V / 12V support on COM1 / COM2 / COM3 / COM4	
UPS Port	Yes, battery (Optional)	
Standard USB Port	6 (5 on the I/O plate, 1 on the front side)	
Proprietary USB Port	1 for side mount options	
VGA Port	D-SUB 15 pins, with 12V power for Posiflex LCD monitor	
CR Port	1, control 2 CR (Optional)	
Extension Slot	PCIe Slot x1, PCIe Riser card (Optional)	
RAID Function	Support RAID 1 (Disk mirroring)	
Physical Dimension		
Dimension (W x D x H in mm)	LCD @ 20°: 378 X 356 X 370 LCD @ 45°: 378 X 366 X 332	
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
Options		
SSD	16 GB minimum	
2nd HDD	2.5" SATA HDD or SSD	
UPS	2300 mAh / 12V	
FA-610A	5V / 12V on COM5 & COM6, and CR port	
2nd LCD display	12" LM-6601	
PD-308 U / S	2 x 20 LCD, default 200 mm pole	
PD-2603 U / S	2 x 20 VFD, default 200 mm pole	
PD-76X3	240 x 64 dot graphic LCD, 200 mm pole	
FA-200	3 tracks and JIS-II or fingerprint sensor	
Certifications		

FT-7715 Series

High Performance FanFree POS Terminal for Harsh Environment



Design and Manufacturing In Taiwan by Posiflex Technology Inc.

2012 FT77Q4C1

** The product information and specifications are subject to change without prior notice.

FT-7715 Series

What do you look for in a POS terminal that is destined for harsh environment? Just reliability? But can you not have more? What about performance? Expandability? And brand reputation?

Look no further! The all new Posiflex FT-7715 FanFree POS terminal has all of above and much more! Looking for performance? Intel Core i5 CPU provides more than enough power for any daily POS related task imaginable. Looking for expandability? Wide array of I/O options, including PCIe expansion slot, are available to meet the different connectivity requirements. Looking for reliability? FT-7715 is designed to run in the harsh and extreme environments, whether it is freezing cold, scorching hot, dusty or greasy. Posiflex's patented FanFree technology and renowned technical prowess saw to it that FT-7715 can function reliably without any hiccup in any environment.

FT-7715 incorporates Intel Core i5 CPU, wide array of connectivity options, and first rate build quality into a robust Aluminum die-casting housing, making it perfectly suited for any harsh environment while still offering unbeatable performance and quality.



Key Features

- ▶ FanFree terminal running Intel Core i5 CPU
- ▶ Built-in RAID function (Disk mirroring)
- ▶ 1 x PCIe extension
- ▶ Internal power adaptor to reduce cable cluster
- ▶ Large footprint for better touch stability
- ▶ Various I/O connectivity options
- ▶ Built-in UPS to provide emergency power in case of power failure (battery optional)

