

KS-7515/7517



Specification	KS-7515	KS-7517
Processor	Intel B830 CPU / 1.8 GHz / 2M cache ; Intel B950 CPU / 2.1 GHz / 2M cache	
System Memory	DDR3 1066 MHz, SO-DIMM socket x 2, max 16 GB	
Storage Device	SATA Storage x 2, factory default: 320GB SATA HDD x 1	
Power Supply	12V DC power adaptor, 80W [Optional 120W when equipping with Posiflex 2nd Display]	12V DC power adaptor, 120W [Optional 150W when equipping with Posiflex 2nd Display]
OS Support	Windows XP Pro / POSReady 2009 / Windows 7 / POSReady 7 / Window Embedded 8.1 Industry / Linux per request	
Display		
LCD	15" TFT LCD, 1024 x 768 resolution	17" TFT LCD, 1280 x 1024 resolution
Touch Function	Resistive, 5-wire, USB Interface / IR touch Bezel-free, Resistive touch Bezel-free, PC touch	Resistive, 5-wire / IR touch
Connectivity		
LAN Port	10 / 100 / 1000Mb	
Serial Port	DB9 x 3, RJ-50 x 1 [Optional RJ-50 to DB9 cable] with 5V / 12V support on COM1 / COM2 / COM3 / COM4	
UPS Port	Yes	
Standard USB Port	7 [6 on the I/O plate, 1 on the left side]	
VGA Port	D-SUB, 15 pins, with 12V support for Posiflex LCD monitor	
Powered USB	Optional 1 x 24V+2 x 12V via GEN8.5 base	
Physical Dimension		
Dimension (W x D x H in mm)	378 x 312 x 340	410 x 312 x 385
Weight (N.W. in Kg)	9.25	11.7
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH [Equipped with HDD] ; 0°C - 50°C, 20%RH - 90%RH [Equipped with SSD]	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	
Options		
SSD	Starting form 16GB	
UPS Battery	2300 mAh/ 12V (GEN8.5 Base required)	
2nd LCD Display	7" LM-6307 10" LM-3010/KS, LM-3210/KS 12" LM-2312X 15" LM-8035X, LM-3015/KS, LM-3215/KS, TM-3015/KS, TM-3215/KS	
Side Attachment	SD-466Z, SD-666W, SD-866W	
Customer Line Display	PD-2604UE, PD-310UE, PD-6307U	



Design and Manufacturing in Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.

2014Q3



POSIFLEX TECHNOLOGY INC.
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller



Affordable Premium Performance

KS-7515/7517

High-end Fan-free POS Terminal

You want a high-end POS terminal with great performance, but premium performance usually costs premium price. Despair no more!

Introducing the newest member of the Posiflex high-end family – JIVA KS-7500 Series!

Like the Posiflex flagship JIVA KS-7700 Series, JIVA KS-7500 Series takes advantage of the Intel Sandy Bridge platform, but with the more economical yet powerful Intel B830 CPU. It also features a new curvier look that adds a little spice to otherwise elegant looking JIVA KS Series exterior. Coupling with Posiflex's patented fan-free design, it assures faster transaction, quieter operation, maximum uptime and minimum maintenance. And most importantly, lower total cost of ownership!



with 2nd display LCD



with customer pole display



with MSR and finger print scanner



with bar code scanner



optional Gen8.5 Base



adjustable LCD

Extensibility & Flexibility



JIVA KS-7500 Series offers premium performance without breaking your bank account, making it the best valued high-end solution in the market.

Highlights of the KS-7515/7517

- ▶ Equipped with up to Intel Pentium B950 2.1GHz CPU (Optional) and DDR3 memory
- ▶ Resistive, IR, Bezel-free Resistive, or Bezel-free PC touch screen (Bezel-free option for JIVA KS-7515 only)
- ▶ 17" LCD 1280 x1024 (JIVA KS-7517) or 15" LCD 1024 x 768 resolution (JIVA KS-7515)
- ▶ UPS (embedded on main board developed by Posiflex) support to avoid sudden loss of power during transaction
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Patented aluminum die casting design for efficient cooling
- ▶ Push-open cover to protect power switch from accidental shutdown
- ▶ Bottom cable guide design and cover for safety and neat outlook