

Product profile

PF2i

RFID Baggage Tag Printer



- **Strong, all-metal construction** and superior throughput for demanding airline and other transportation applications
- **Compact size** fits space-constrained environments
- **Exceptional reliability** ensures low cost of ownership
- **Smart Printing capabilities** support stand-alone printer applications, eliminating PC expense and complexity
- **Secure wireless connectivity:** CCX and WiFi® certified with WPA2
- **Integrated Ethernet**, USB host and device, and serial interface standard
- **Internet Protocol v6 (IPv6)** support
- **RFID – IATA 1740c** Compliant

A member of the smartest bar code printer family on the market, the Intermec PF2i is flexible and programmable, enabling transportation industry customers to optimize their printing operations, streamline deployment, and achieve quick return on investment. Built to meet the needs of mission-critical applications, the rugged PF2i delivers advanced, secure connectivity and the latest network protocols, ensuring peace-of-mind today and a reliable, scalable solution for the long haul. The compact PF2i RFID Baggage Tag Printer is part of Intermec's complete line of smart, strong and secure industrial printers.

Smart

The PF2i's smart design features support increased productivity in demanding environments. As a Smart Printer, the PF2i can host stand-alone applications, developed through Intermec Fingerprint programming language, that reduce errors and streamline operational processes. Smart Printers can eliminate the PC and control other devices directly, improving efficiency and decreasing infrastructure costs and complexity.

The PF2i's integrated device management and diagnostic capabilities, provided through Intermec SmartSystems™ and Wavelink Avalanche™, reduce downtime and simplify deployment. Its secure, industry-standard connectivity options

support easy integration and fast deployment.

Strong

Rugged and compact, the PF2i is ideal for demanding airline and transportation applications where space is limited and downtime is not an option. With few parts to maintain and exceptional reliability, the PF2i ensures low cost of ownership. Its patented RFID radio module encodes and verifies the RFID tags within the media ensuring a viable bag tag every time.

The PF2i can print on RFID enabled external fan-folded bag tags as well as non-RFID credit card size boarding tickets. It can take advantage of the latest RFID tag technologies including ISO 18000-6B and 6C / EPC Gen 2, and provides a seamless transition from older printers (such as the BT201). Because it is available in a variety of UHF frequencies, the PF2i is ready for use in most regions of the world.

Secure

Multiple interface options are available, including the highest level of secure wireless connectivity (WPA2). The industry's only printers available with WiFi- and CCX-Certification, Intermec industrial printers help maintain wireless network integrity and reduce configuration time. Every printer ships with Ethernet connectivity, as well as with emerging network protocol IPv6, ensuring long-term,

enterprise scalability. Other connectivity options provide additional integration flexibility.

The standard CompactFlash™ memory slot is complemented by new USB host and device support. Handy, inexpensive and PC-compatible, CompactFlash and USB memory technologies provide extra storage for Fingerprint programs, layouts, graphics*, fonts and firmware upgrades.

The PF2i can be complemented by the Intermec PF4i, a four-inch printer ideal for printing full size boarding passes which leverages the same hardware and software, for maintenance cost efficiency.

* Fingerprint only

Description

The PF2i Baggage Tag Printer is an RFID-enabled direct thermal printer designed for encoding and printing RFID bag tags as well as non-RFID tickets.

Physical Characteristics

Length: 397 mm (15.6 in)
Height: 178 mm (7 in)
Height (big top): 205 mm (8.1 in)
Width: 194 mm (7.6 in)
Weight: 5.5 kg (12 lbs.)

Print Specifications

Max. Width: 56 mm (2.2 in)
Max. Length: 4095 mm (161.2 in)

RFID Standards & Frequencies

Compliant with IATA/AEA baggage tag specifications including IATA 740 and 1740c
Supports ISO 18000-6B and 18000-6C / EPC Class 1 Generation 2
865-928 MHz radio configured to comply with local UHF RFID regulations including FCC and ETSI

Print Speed

100 - 200 mm/s (4 - 8 ips) variable

Print Resolution

8 dots/mm (203 dpi)

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

North Latin America

Headquarters Office
Mexico
Phone: +52 55 52-41-48-00
Fax: +52 55 52-11-81-21

South Latin America

Headquarters Office
Brazil
Phone: +55 11 5502.6770
Fax: +55 11 5502.6780

Europe/Middle East & Africa

Headquarters Office
Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office
Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Media

Type: Labels & Tags
Max/ Min Width: 60/ 25.4 mm (2.36/ 1 in)
Thickness: 3.0 to 7.5 mil
Configuration: Roll-fed or fanfold
Sensing: Gap, notch, black mark, continuous
Label Roll Max Diameter (long door): 152.4 mm (6 in)
Label Roll Max Diameter (short door): 213 mm (8.38 in)
Label Roll Core: 38-76mm (1.5-3 in)

Type: Ribbons

Roll Max Diameter: 65 mm (2.56 in), approx. 225m
Core ID: 25.4 mm (1")
Type: Wax, mid-range, resin

Genuine Intermec Media: www.intermec.com/media

Interfaces

Standard:

- Ethernet 10/100 Mbps
- RS-232, up to 115.2 kB/s

Supported Serial Protocols:

- Fingerprint/Direct Protocol: XON/XOFF, ENQ/ACK, DTR, RTS/CTS
- IPL: XON/XOFF, Intermec Std. Protocol
- USB 2.0

Optional:

- Parallel IEEE 1284
- Industrial Interface (8 digital in/out, 4 analog relays, 1 RS232/422/485 port)
- Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop

Wireless:

- IEEE 802.11 b/g
- Wi-Fi Certified, CCX (Cisco®) version 3 Certified
- WEP, WPA, WPA2, 802.11x (EAP-TTLS, LEAP, PEAP, FAST), 802.11i
- Multiple industrial antenna options for maximized coverage

Supported Protocols:

TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.) LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMPv3, SMTP.SNMP-MIB II supported (over UDP/IP), private enterprise MIB included
Supports IPv4 and IPv6

Software

Printer Command Languages:

- IPL
- Fingerprint/Direct Protocol
- ZSim (ZPL)
- DSim (DPL)
- XML enabled for SAP® All and Oracle® WMS

Applications / Drivers:

- InterDriver™ Windows printer driver
- Intermec label design and print package
- PrintSet for printer configuration

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
FreePhone ROW:
00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Development Software:

- Intermec Fingerprint Application Builder™ (IFAB) (RFID libraries included)

Device Management Support:

- SmartSystems™
- Wavelink Avalanche™

Customized:

- Specific Airline applications bases on std AEA
- Any other specific, non AEA, Airline application.

Bar Code Symbolologies

All major 1D and 2D symbolologies are supported.

Fonts

Scalable fonts including CP1252
Font cache for maximum performance
Non-Latin fonts and legacy fonts available

Graphics

Supports PCX file format. (Fingerprint Only)
Other formats supported with Label Generation Tools

Memory

Standard: 16MB Flash memory, 32MB SDRAM, 1 Compact Flash slot
Available: 1GB CompactFlash memory, multi-GB USB memory device (FAT16/FAT32 USB drivers supported)

Keypad Control Panel

Interactive numeric keypad control panel

Power Supply

AC Voltage: 90 to 265 VAC, 45 to 65Hz
PFC Regulation: IEC 61000-3-2
Power Consumption: Standby 15W; Peak 300W

Operating Environment

Ambient Operating Temperature:
+5°C to +40°C (+41°F to +104°F)
Storage Temperature: -20°C to +70°C (-4°F to +152°F)
Humidity: 20 to 80% non-condensing

Regulatory Approvals

CE (EN55022 Class A), FCC Class A, UL/cUL, C-Tick

Options

Integral self-strip unit with liner take-up, Label Taken Sensor (LTS), Compact Flash (CF) memory, various international double byte fonts, alphanumeric keyboard*, parallel interface board, additional serial interface board*, industrial interface board*, applicator interface board*, real time clock, media supply hub, label low sensor

*Not applicable when using IPL firmware



Copyright © 2009 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611773-01D 10/09

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

