

XP-2300/2000 Series

www.posiflex.com

POSIFLEX
Your Success is Our Vision



Specification	XP-2008H	XP-2010H	XP-2012H	XP-2308H	XP-2312H
Processor	Intel Celeron M 600 MHz, 512 K Cache CPU				
System Memory	DDR2 400 MHz, SO-DIMM x 1, max 2 G, default 512 MB				
Storage Device	DOM 1 GB or 2.5" SATA HDD (Optional) or SSD kit (Optional)				
Power Supply	12V DC Power adaptor, 60W		12V DC Power adaptor, 80W		
Audio	Buzzer Only				
OS support	Linux, WinCE, WinXP PRO, POSReady (Support XP & POSReady by upgrade to SSD or 2.5" SATA HDD)				
Display					
LCD	8" TFT LCD, 800 x 600 resolution	10.4" TFT LCD, 800 x 600 resolution	12" TFT LCD, 1024 x 768 resolution	8" TFT LCD, 800 x 600 resolution	12" TFT LCD, 1024 x 768 resolution
Touch Function	Resistive, 5-wire, USB Interface				
Brightness Control	By software control			By software control	
Tilt Adjustment	From 14° to 55°				
Connectivity					
LAN Port	10 / 100 Mb				
Serial Port	DB9 x 1, with 5V support				
Standard USB Port	4				
VGA Port	D-SUB 15 Pin, with 12V power for Posiflex LCD Monitor				
CR Port	1				
Printer					
Printer build in	2" Thermal Printer (60 mm / sec), 58 mm paper width			3" thermal printer (60 mm / sec), 80 mm paper width	
Cutter	Manual Cutter, Auto cutter (Optional)		Auto Cutter		
Physical Dimension					
Dimension (W x D x H in mm)	325 x 386.2 x 249.6	325 x 386.2 x 298.1	325 x 386.2 x 331.2	325 x 386.2 x 249.6	325 x 386.2 x 331.2
Weight (N. W. in kg)	4.15	5.75	6.54	4.15	6.54
Environment					
Operation Condition	0°C - 40°C, 20%RH - 90%RH				
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH				
Options					
MSR	Integrated, 2 or 3 tracks and JIS-II				
KB	84 keys mini KB with USB Interface				
PD-2605 / PD-2605U	2 x 20 VFD, default 200 mm pole				
PD-2606U	2 x 20 VFD, rear mount				
PD-309 / PD-309U	2 x 20 LCD, default 200 mm pole				
PD-330U	2 x 20 LCD, rear mount				
PD-76X4	240 x 64 dots Graphics LCD, default 200 mm pole				
SSD	8 GB Minimum				
2.5" SATA HDD	80 GB Minimum				
LM-2208	8" TFT LCD, 800 x 600 resolution	N/A	N/A	8" TFT LCD, 800 x 600 resolution	N/A
LM/TM-2212	N/A	12" 2nd LCD Display or touch LCD Display with attachment SD-300	N/A	N/A	12" 2nd LCD Display or touch LCD Display with attachment SD-300
Certifications					

XP-2300 / 2000 Series

All-in-One Fan-Free POS Terminal



Design and Manufacturing In Taiwan by Posiflex Technology Inc.
** The product information and specifications are subject to change without prior notice.

2011 XP2000Q1C1

POSIFLEX Posiflex Technology, Inc.
Head Quarter
6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com

XP-2300 / 2000 Series

Posiflex delivers the fan-free XP-2300 /2000 series as valued mini POS terminal.

The all-in-one POS terminal XP-2300 / 2000 series combine touch screen, thermal printer, MSR in a fan-free system. It is affordable in a well-executed design for general purpose applications.

The XP-2300 /2000 series are suitable for small and medium retailers to serve customers effectively.



Key Features

- ▶ Resistive touch screen : 12" LCD 1024 x 768, 10.4" LCD 800 x 600 or 8" LCD 800 x 600 resolution
- ▶ Equipped with Intel Celeron-M 600 MHz CPU
- ▶ All-in-one integrated system with touch screen, thermal printer and MSR for space saving
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Aluminum die casting design for efficient cooling
- ▶ 2" or 3" thermal printer with auto cutter
- ▶ Thermal printer with "one-button cutter blade retract" design to clear paper jam easily (Excluding XP-2008H)
- ▶ Special "drop-load" design for easy printer paper roll loading
- ▶ User-friendly mechanism for system upgrade and easy maintenance
- ▶ High quality, rock solid design with easy maintenance in mind

